



# EMPLOYEE ATTENDANCE WITH TEMPERATURE & FACE SCANNING

*Integrated with Cloud Attendance, Payroll & Leave Software*



Palm Recognition



Face Recognition



Temperature & Mask Detection

**Compatible with SafeEntry Contact Tracing**

## SPECIFICATIONS

Display	5-inch Touch Screen
Face Capacity	6,000
Palm Capacity	3,000
Fingerprint Capacity	6,000
Transactions	200,000
Operation System	Linux
Standard Functions	ADMS, T9 Input, DST, Camera, 9-digit User ID, Access Levels, Groups, Holidays, Anti- passback, Record Query, Tamper Switch Alarm, Multiple Verify Modes.
Hardware	900MHz Dual Core CPU, Memory 512MB RAM/ 8G Flash, 2MP WDR Low Light Camera, Adjustable Light Brightness LED
Communication	TCP/IP, WiFi (Optional), Wiegand input / output, RS485
Access Control Interface	3rd Party Electric Lock, Door Sensor, Exit Button, Alarm output, Auxiliary Input
Facial Recognition Speed	≤1s
Biometrics Algorithms	ZKFace V5.8 & ZKFinger V10.0 & ZKPalm V12.0
Power Supply	12V 3A
Operating Humidity	10% - 90%
Operating Temperature	-10°C ~ 45°C (14°F ~ 113°F)
Dimensions	91.93 * 220 * 22.5 (mm)

SINGAPORE | MALAYSIA | HONG KONG | INDIA

An Initiative Of:

